



PIGMENTOS METÁLICOS
METALLIC PIGMENTS

PIGMENTOS DE ALUMINIO Y BRONCE
ALUMINUM AND BRONZE PIGMENTS

Base agua
Waterbased



Together creating
a brilliant world

OFICINAS CORPORATIVAS

Azahares No. 26 Desp. 203
Col. Santa María Insurgentes
C.P.: 06430, México D.F.
Tel: (52)-(55) 1946.0850
5583.0557
mail: info@metapol.com.mx

HEADQUARTERS

Azahares No. 26 Desp. 203
Col. Santa María Insurgentes
Z.C.: 06430, México D.F.
Ph: (52)-(55) 1946.0850
5583.0557
mail: info@metapol.com.mx

PLANTA

Carretera a Veracruz Km.144
San Cosme Xaloztoc
Tlaxcala, México
C.P.: 90460
Tel: (241) 413.0126
Fax: (241) 413.0156

PLANT

Carretera a Veracruz Km.144
San Cosme Xaloztoc
Tlaxcala, México
Z.C.: 90460
Ph: (241) 413.0126
Fax: (241) 413.0156



metapol.com.mx



METALLIC PIGMENTS FOR WATER BASED

PRODUCTS

PRODUCT	FORM	D-50	%NV	Recommended Ph
CD 1525 WH-4	Flake	22	65%	5-9
CD 2410 WH-4	Flake	10	65%	
Alu D1060 WHR	Dollar	60	65%	
Alu D1050 WHR	Dollar	50	65%	
Alu D2036 WHR	Dollar	36	65%	
Alu M1050 WH-4	Mix	50	65%	
Alu F2030 WH-4	Flake	30	65%	
Hydropaste U2530	Flake	48-53	85%	Neutral, insitu applications
Hydropaste B4555	Flake	37-44	85%	
Hydropaste R7080	Flake	20-25	85%	

*Hydropaste U, B, R available in Rich Gold, Pale Gold, Rich Pale Gold and Copper



SiO and Brio LINE

PRODUCT	TYPE	FORM	D-50	%NV	L/NL
SiO D5570 WHS	Paste	Dollar	55	70%	NL
SiO D4470 WHS	Paste	Dollar	44	70%	NL
SiO D3670 WHS	Paste	Dollar	36	70%	NL
U 5085 WHS*	Paste	Flake	50	85%	NL
B 3285 WHS*	Paste	Flake	32	85%	NL
I 1485 WHS*	Paste	Flake	14	85%	NL
SiO D5530 WGS	Suspension	Dollar	55	30%	NL
SiO D4430 WGS	Suspension	Dollar	44	30%	NL
SiO D3630 WGS	Suspension	Dollar	36	30%	NL
U 5030 WGS*	Suspension	Flake	50	30%	NL
B 3230 WGS*	Suspension	Flake	32	30%	NL
I 1430 WGS*	Suspension	Flake	14	30%	NL

*Brio U, B, I available in Rich Gold, Pale Gold and Copper.

RECOMMENDATIONS FOR USE

- The water-based pastes should be pre-dispersed using water and / or co-solvent in a 1: 1 or 1: 2 ratios by stirring at low revolutions, avoiding the use of sharp or cutting discs that cause fractures to the flakes; incorporate until obtaining a homogeneous mixture.
- It is important to check the compatibility of the additives to obtain homogeneous finishes without film defects or lumps presence.
- It is recommended to evaluate the behaviour of the vehicle and / or resin with the water based pastes to determine the stability of the formulations in storage, which depends on the nature and technology of the final coating.
- After formulating, leave the containers open for 24 hours to prevent inflation by gas accumulation.
- Work the paste at room temperature (20-25 °C).

NOTES

* Prior to use and application of this product, consult the technical data sheet to consider other technical requirements and safety precautions.

*The information provided corresponds to the current technology, knowledge and experience. All the indications are given as guiding information and / or advice, so that METAPOL, S.A. DE C.V., disclaims any liability for its misuse.

