

Pinturas decorativas Decorative Coatings



metapol.com.mx



OFICINAS CORPORATIVAS

Azahares No. 26 Desp. 203 Col. Santa María Insurgentes C.P.: 06430, México D.F. Tel: (52)-(55) 1946.0850 5583.0557 mail: info@metapol.com.mx

HEADQUARTERS

Azahares No. 26 Desp. 203 Col. Santa María Insurgentes Z.C.: 06430, México D.F. Ph: (52)-(55) 1946.0850 5583.0557 mail: info@metapol.com.mx

PLANTA

Carretera a Veracruz Km.144 San Cosme Xaloztoc Tlaxcala, México C.P.: 90460 Tel: (241) 413.0126 Fax: (241) 413.0156

PLANT

Carretera a Veracruz Km.144 San Cosme Xaloztoc Tlaxcala, México Z.C.: 90460 Ph: (241) 413.0126 Fax: (241) 413.0156









PRODUCTS

ALU LINE

PRODUCT	TYPE	FORM	D-50	%NV
Alu D1070	Non Leafing Paste	. Silver Dollar	70	70%
Alu D1054	Non Leafing Paste		54	70%
Alu D2034	Non Leafing Paste		34	70%
Alu D3027	Non Leafing Paste		27	70%

GAP LINE

PRODUCT	TYPE	D-50	%NV	Solvent
Gap 2		22	65%	
Gap 275	Leafing Paste	22	75%	Aliphatic
Gap 3		17	65%	

CD LINE

PRODUCT	TYPE	D-50	%NV	Solvente	
CD 1525	Leafing Dispersion	22	65%	Aliphatic-	
CD 1917		17	62%	Aromatic	

CUBRIO LINE

PRODUCT	TYPE	D-50	%NV	TONE
U 2530	Leafing	48-53	100%	Rich Gold,
B 4555	powder	37-44	100%	Rich Pale Gold,
R 7080		20-25	100%	Pale Gold and Copper

COLORED BRONZE POWDERS

PRODUCT	TYPE	D-50	%NV	TONE
U 2530	Leafing powder	48-56	100%	Royal Lemon, English Green, Ducat, Old Gold, Mandarine, Fire Red, Wine, Lavender
U 3045	porruer	48-52	100%	Karat

SIO-BRIO LINE

PRODUCT	TYPE	FORM	D-50	%NV	L/NL
SiO D5570 WHS	Paste	Dollar	55	70%	NL
SiO D4470 WHS	Paste	Dollar	44	70%	NL
SiO D3670 WHS	Paste	Dollar	36	70%	NL
U 5085 WHS*	Paste	Flake	50	85%	NL
B 3285 WHS*	Paste	Flake	32	85%	NL

* Available in Rich Gold and Pale Gold tones

ALU LINE - WATER BASED

PRODUCTO	FORM	D-50	%NV	Recomended pH	
Alu D1060 WHR	Dollar	60	65%		
Alu D1050 WHR	Dollar	50	65%		
A l u D2036 WHR	Dollar	36	65%	5-9	
A l u M1050 WH-4	Mix	50	65%		
Alu F2030 WH-4	Flake	30	65%		
Hydropaste U2530*	Flake	48-53	85%	Neutral, in situ applications	
Hydropaste B4555*	Flake	37-44	85%		

^{*} Available in Rich Gold, Pale Gold, Pale Rich Gold and Copper

RECOMMENDATIONS FOR USE

- Metallic pigments are directly incorporated into the vehicle by mixing slowly at low speeds of less than 400 rpm using flat disk propellers or dull blades to avoid damaging the flakes, slowly adding the pigment to minimize dust cloud generation.
- Mixing equipment must be kept grounded.
- To obtain stable formulations during storage, the use of vehicles or resins with a low acidity index is recommended to avoid reactions with the metal causing variations in the tone, loss of brightness or even paint gelation or hardening.
- Carrying out pigment stability tests with the vehicle is desirable.
- To achieve a good coverage in the formulation, it is recommended to use 15 to 22% of pigment over the total formulation, however the customer must adjust to their own needs.

NOTES

- * Prior to use and application of this product, consult the technical data sheet to consider other technical requirements and safety precautions.
- *The information provided corresponds to the current technology, knowledge and experience. All the indications are given as guiding information and / or advice, so that METAPOL, S.A. DE C.V., disclaims any liability for its misuse.



